



WELDING BLANKET

FiremanBrand

WELDING BLANKET

FIREMANBRAND EYELETTED BLANKET TECHNICAL INFORMATION

- Highly flame resistant characteristics. Suitable for short – term exposure to flames/heat. 550gsm
- Very low heat shrinkage. For example, a blanket exposed to 240deg.c for 2 hours will shrink by less than 1 ½ percent.
- The limited oxygen index (LOI) is above 50 %, meaning that the air would have to contain at least 50 % pure oxygen in order to ignite the blanket.
- The blanket is non – toxic and does not emit any smoke, even when exposed to fire for an extended period.
- It is soft and drapes easily around objects.
- It is light, non – abraive and does not melt.
- It has no competitors in the field of protection against heat, flames and hot metal splashings .Fibre glass, asbestos and ceramic blankets resist heat but they are heavy and abraive. In addition, they are not environmentally friendly. In fact, fibre glass and asbestos are downright dangerous.
- It carries The Proudly South African logo.



SAPPHIRE FLAME RETARDANTS CC
2 MYHOF ROAD CLAREMONT 7700 P.O.BOX 36264 GLOSDERRY 7702
TEL: 021 6837815 FAX: 0865471319
e-mail: sapphire@sapphireflame.co.za Website: www.sapphireflame.co.za
VAT REG. NO. 4500207834 CC REG. No:2001/011463/23